

# Master HP FC UL



DATA CENTER



MEDICAL



INDUSTRIAL



TRANSPORTATION



EMERGENCY LIGHTING



ONLINE



Tower



**3:3** 80-200 kVA

Voltage and Frequency Converter



Service 1st start



SmartGrid ready



## HIGHLIGHTS

- High efficiency
- IGBT-based rectifier technology
- Output voltage: 400 V - 50Hz
- Galvanic isolation
- High overload capacity

The high levels of quality, reliability and energy savings offered by the Master HP range of UPS have been extended to include frequency converter 480 V - 60 Hz input /400 V - 50 Hz output certified as UL, with power ratings from 80 to 200 KVA. The typical application of such Frequency Converters is the power supply of the loads at 400 V, 50 Hz as for example imported from other countries. The FC units can work with or without battery. With its double conversion on-line technology based entirely on IGBT and digital signal processors (DSP), the Master HP FC UL range ensures maximum critical load protection, with VFI SS 111 classification (Voltage and Frequency Independent) in accordance with IEC EN 62040-3. This range

is designed using a new configuration that includes an IGBT sinusoidal input rectifier. Unique in its design, double conversion technology with galvanic isolated output guarantees a quality power supply that is completely protected from all electrical anomalies at the input.

### Complete galvanic separation

Master HP FC UL feature an output isolation transformer (delta zig/zag type) on the inverter as part of the inverter circuit inside the FC cabinet, providing galvanic isolation between the load and the battery with improved versatility in system configuration, allowing:

- Complete FC output galvanic isolation for

critical infrastructures from the battery DC power source;

- No neutral input connection is required at the rectifier input stage;
- No effects to the FC output performance or reduced impact of the inverter power components whilst supplying specific loads; in addition the inverter transformer minimizes the impact of third harmonic disturbances, prevents the effects of energy back-feed into the inverter when supplying industrial load applications and can supply unbalanced loads.
- High inverter short circuit current to clear faults which occur between phase and neutral on load side (up to three times nominal current).

Output transformer housed within a cabinet which allows for a significant reduction in the footprint and provides space savings.

### Zero impact source

The Master HP FC UL features the added advantages of the Zero Impact Source formula offered by an IGBT-based rectifier assembly. This eliminates problems connected with installation in networks with limited power capacity, where the FC is supplied by a generator set or anywhere there are compatibility problems with loads that generate current harmonics. Master HP UL series FC have zero impact on the power supply source, whether it is a mains grid or generator set:

- input current distortion < 3%
- input power factor 0.99
- power walk-in function that ensures progressive rectifier start up
- start-up delay function, to restart the rectifiers when mains power is restored if there are several FC in the system.

This provides savings in installation costs via:

- a smaller electrical infrastructure.
- smaller circuit protection devices
- less wiring.

### Battery care system: maximum battery care

Master HP FC UL uses the Battery Care System, which optimises battery performance in order to extend the battery life for as long as possible.

### Main features

- Compact size: e.g.: only 1318 in2 for Master MHT FC 200 UL
- Reduced weight for transformer based FC
- Double load protection, both electronic and galvanic, towards the battery.

The entire Master HP FC UL range is suitable for use in a wide range of applications. Thanks to the flexibility of configuration, available options and accessories, it is suitable for supplying any type of load, e.g. capacitive loads such as blade servers, rather than motor drivers or any other critical vertical application. Power supply reliability and availability are ensured for critical applications by distributed parallel configurations of up to 8 units, for redundant (N+1) or power parallel configurations.

### Advanced supervision

Master HP series FC have a front panel mounted graphic display providing FC information, measurements, status updates and alarms in different languages, with wave form displays including voltage/current and providing a kWh reading that can be used to measure IT loads and calculate a Data Center PUE (power usage effectiveness) ratio.

## OPTIONS

### SOFTWARE

PowerShield<sup>3</sup>

PowerNetGuard

### ACCESSORIES

NETMAN 204

Multi I/O (Relay Alarm card and generator Interface)


### PRODUCT ACCESSORIES

Parallel configuration kit (Closed Loop)


Fully configured battery systems with appropriate autonomy

## DIMENSIONS


### MHT FC 80 UL - MHT FC 100 UL



### MHT FC 125 UL - MHT FC 160 UL MHT FC 200 UL



### MHT FC 125 UL TCE - MHT FC 160 UL TCE MHT FC 200 TCE



MODELS	MHT FC 80 UL	MHT FC 100 UL	MHT FC 125 UL	MHT FC 160 UL	MHT FC 200 UL
<b>INPUT</b>					
Nominal voltage	480 Vac three-phase + N				
Frequency	45 - 65 Hz				
Power factor	> 0.99				
Harmonic current distortion	<3% THDi				
Soft start	0 - 100% in 125" (selectable)				
Frequency tolerance	± 2% (selectable from ± 1% to ± 5% from front panel)				
<b>BATTERIES</b>					
Type	VRLA AGM / GEL; NiCd; Li-ion; Supercaps and Flywheel				
Ripple current	Zero				
Recharge voltage compensation	-0.5 Vx°C				
<b>OUTPUT</b>					
Nominal power (kVA)	80	100	125	160	200
Active power (kW)	72	90	112.5	144	180
Number of phases	3 + N				
Nominal voltage	400 Vac three-phase + N				
Static stability	± 1%				
Dynamic stability	from ± 5% to ± 1% in 20 ms				
Voltage distortion	< 1% with linear load / < 3% with non-linear load				
Crest factor	3:1 lpeak/lrms				
Frequency stability on battery	0.05%				
Frequency	50 Hz				
Overload	110% for 60'; 125% for 10'; 150% for 1'				
<b>INFO FOR INSTALLATION</b>					
Weight (lbs [kg])	1610 [730]	1742 [790]	1851 [840]	2138 [970]	2447 [1110]
Weight with TCE (lbs [kg])	-	-	2204 [1000]	2524 [1145]	2799 [1270]
Dimensions (WxDxH) (inches [mm])	31.5 x 33.5 x 75 [800 x 850 x 1900]		39 x 33.5 x 75 [1000 x 850 x 1900]		
Dimensions with TCE and Maintenance bypass (WxDxH) (inches [mm])	-	-	55 x 33.5 x 75 [1400 x 850 x 1900]		
Remote signals	dry contacts (configurable)				
Remote controls	ESD (configurable)				
Communications	Double RS232 + dry contacts + 2 slots for communications interface with SNMP, Modbus, and Bacnet Protocols				
Operating temperature	0 °C / +40 °C (32 to 104 °F)				
Relative humidity	<95% non-condensing				
Color	Black				
Noise level at 1 m	65 dBA			68 dBA	
IP rating	IP20				
Standards	UL Standard 1778: 2nd edition 80 and 100 kVA, 5th edition from 125 to 200 kVA and CAN/CSA C22.2; From 125 to 200 kVA: UL 60950-1 1: Information Technology Equipment - Safety - Part 1: General Requirements National Electrical Code (NFPA-70); FCC Part 15 Subpart J class A – Radio Frequency; IEC 62040-3;				
Classification in accordance with IEC 62040-3	(Voltage Frequency Independent) VFI - SS - 111				
Transport	Pallet Jack or Fork Lift				

**RPS S.p.A.**

**ITALY**

**LEGNAGO (VR)**

**Head Office**

Viale Europa, 7  
37045 LEGNAGO (Verona)  
Tel +39 0442 635811  
www.riello-ups.com  
riello@riello-ups.com

**CORMANO (MI)**

**Sales Office**

Via Somalia, 20  
20032 CORMANO (Milano)  
Tel +39 02 663271



**PRE-SALES SUPPORT**

(TEC)  
tec@riello-ups.com



**AFTER-SALES SUPPORT**

(UPService)  
service@riello-ups.com

## Worldwide Subsidiary Companies

**USA**

**RPS AMERICA**

8808 Beckett Rd  
West Chester, OH 45069  
Tel +1-513-282-3777

**UNITED KINGDOM**

**RIELLO UPS Ltd.**

Unit 50 Clywedog Road North  
Wrexham Industrial Estate  
Wrexham LL13 9XN  
Tel +44 800 269 394

**CONSTANT POWER SERVICES Ltd.**

Riello House, Works Road,  
Letchworth  
SG6 1AZ Hertfordshire  
Tel +44 330 1230125

**GERMANY**

**RIELLO UPS GmbH**

Wilhelm-Bergner-Str. 9b  
21509 Glinde  
Tel +49 40 / 527 211-0

**RIELLO POWER SYSTEMS GmbH**

Neufahrner Str. 12b  
85375 Neufahrn/Grüneck  
Tel +49 8165 / 9458-0

**FRANCE**

**RIELLO ONDULEURS S.a.r.l.**

2/4 Rue du Bois Chaland,  
ZAC du Bois Chaland  
91090 Lisses  
Tel +33 1 60 875454

**SPAIN**

**RIELLO ENERDATA s.l.u.**

C/ Labradores,  
13 Parque Empresarial  
Prado del Espino  
28660 Boadilla del Monte  
Madrid  
Tel +34 916 333 000

**RIELLO TDL s.l.**

C/Berguedà, 6 bis  
Pol. Ind. Plà de la Bruguera  
08211 Castellar del Vallès, Barcelona  
Tel +34 902 02 66 54

**ROMANIA**

**RIELLO UPS ROMANIA S.r.l.**

Str. Varsovia Nr. 4  
307160 Dumbravita  
Timis County - Romania  
Tel +40 256 214 681

**POLAND**

**RIELLO DELTA POWER Sp. z o.o.**

ul. Krasnowolska 82 R  
02-849 Warszawa  
Tel +48 22 379 17 00

**AUSTRALIA**

**RIELLO UPS AUSTRALIA Pty. Ltd.**

Unit 22/80 Box Road  
Taren Point NSW 2229  
Tel +61 2 9531 1999

**ASIA PACIFIC**

**RIELLO UPS SINGAPORE Pte Ltd.**

No. 506 Chai Chee Lane,  
#07-01, Singapore 469026  
Tel +65 6441 2005

**CHINA**

**Riello UPS (Asia) Co., Ltd.**

Bolg2, No.451 Duhui Road,  
Minhang District-201108  
Shanghai  
Tel +86 21 50464748

**INDIA**

**RIELLO POWER INDIA Pvt. Ltd.**

287-288 Udyog Vihar, Phase II  
122015 Gurgaon (HR)  
Tel +91-124-4111999



Follow us on Social Networks

